



## Mechanical Suspension Seat Maintain Equipment Railway Inspection Vehicle Seat

Our Product Introduction

### Basic Information

- Place of Origin: Shaanxi China, Shaanxi China
- Brand Name: Botai
- Certification: ISO9001:2015
- Model Number: M801-24
- Minimum Order Quantity: 1 set
- Price: \$169~\$260/set
- Packaging Details: Carton
- Delivery Time: 10-15 days
- Payment Terms: T/T
- Supply Ability: 100Sets Per Week



### Product Specification

- Product Name: Mechanical Suspension Seat Maintain Equipment Railway Inspection Vehicle Seat
- Product Model: M801-24
- Product Size: 570\*570\*1340-1400mm
- Head Restraint Adjustment: 3 Gears Adjustable, 25mm For Each Gear
- The Back Elevation Angle Is 80-120° Adjustable:
- Port: Shanghai/Guangzhou
- Highlight: **Black Mechanical Suspension Seat, Detection Car Seat, Inspection Vehicle Seat**

for more products please visit us on [vehicle-seats.com](http://vehicle-seats.com)

## Product Description

### Mechanical Suspension Seat Maintain Equipment Railway Inspection Vehicle Seat Details

Product Name	Mechanical Suspension Seat Maintain Equipment Railway Inspection Vehicle Seat
Place of Origin	Shaanxi China
Product Model	M801-24
Scope Of Application	Universal
Product Size	570*570*1340-1400 mm
Product Material	PU/Leather/Fabric
Product Color	Black
Backrest size	480*630 mm
Cushion size	480*470*(490-550)mm
Adjustable Backrest Elevation	80-120°
Horizontal adjustment	Front 105mm, Rear 120mm 23 adjustable
Weight Adjustment	40-130kg
Bottom Connecting Hole Spacing	Left And Right 216mm* Front And Rear 295.5mm

### Mechanical Suspension Seat Maintain Equipment Railway Inspection Vehicle Seat Application Scenarios

The Company's main products have been widely used in automobiles, trains, construction machinery, coal mine equipment, industrial linkage devices and ferries.

### Mechanical Suspension Seat Maintain Equipment Railway Inspection Vehicle Seat Technology Control

1. The outer fabric of the seat should be firmly stitched, the stitching part should not allow the cable head to be exposed, the seam off line and jumper phenomenon, the surface of the seat after assembly should be full and clean, without deformation, discoloration, wrinkling, external leakage, decolorization, stains, damage and scratches.
2. After the seat is assembled, the slide adjustment, backrest adjustment, and headrest adjustment should be flexible and reliable, without interference.
3. The frame and the leakage parts should be treated with rust prevention, in line with the factory requirements, and electroplating and chemical treatment should be in line with the factory
4. Each connection of the seat should be firmly connected and reliable. Each welding component shall not have welding dislocation, welding, welding and other defects.

### Mechanical Suspension Seat Maintain Equipment Railway Inspection Vehicle Seat Size



**Shaanxi Botai Automobile Accessories Co.,Ltd.**



15319910265



41318225@qq.com



vehicle-seats.com

140 meters west of intersection of Sunwu Road and Lane 4, Zhongjie, Weiyang District, Xi 'an, Shaanxi, China