



Air Suspension Driver Seats Heavy Plant Industry Vehicle Driver Seat

Our Product Introduction

for more products please visit us on vehicle-seats.com

Basic Information

- Place of Origin: Shaanxi China
- Brand Name: Botai
- Certification: ISO9001
- Model Number: A800-24
- Minimum Order Quantity: 1 set
- Packaging Details: 6-8 Cartons Packed To A pallet
- Delivery Time: 10-15days
- Payment Terms: T/T
- Supply Ability: 100Sets Per Week



Product Specification

- Name: Air Suspension Driver Seats For Heavy Plant Industry Vehicle Driver Seat
- Material: PU Or Leather/Fabric
- Size: 500*570*1140-1200mm
- Color: Black Or Customzied
- Product Model: A800-24
- Cushion Size: 480*470*290-350mm
- Highlight: **Heavy Plant Industry Vehicle Driver Seat, Heavy Plant Industry Air Suspension Seat, Vehicle Driver Air Suspension Seat**

Product Description

Air Suspension Driver Seats For Heavy Plant Industry Vehicle Driver Seat Details :

Product Name	Air Suspension Driver Seats For Heavy Plant Industry Vehicle Driver Seat
Place of Origin	Shaanxi China
Product Model	A800-24
Product Material	PU/ Leather/Fabric
Product Color	Black
Backrest Size	480*630mm
Cushion Size	480*470*290-350mm
Adjustable Backrest Elevation	80-120°
High-low Adjustment	60mm
Horizontal adjustment	Front105mm, Rear 120mm
Bottom Connecting Hole Spacing	Left and right 216mm front and back 295.5mm or as yours

Product Technology:

1. After the seat is assembled, the slide adjustment, backrest adjustment, and headrest adjustment should be flexible and reliable, without interference.
2. The outer fabric of the seat should be firmly stitched, the stitching part should not allow the cable head to be exposed, the seam off line and jumper phenomenon, the surface of the seat after assembly should be full and clean, without deformation, discoloration, wrinkling, external leakage, decolorization, stains, damage and scratches.
3. The skeleton and the leakage parts should be treated with rust prevention, in line with the factory requirements, and electroplating and chemical treatment should be in line with the factory
4. Each connection of the seat should be firmly connected and reliable. Each welding component shall not have welding dislocation, welding, welding and other defects.
5. The safety of the seat should meet the requirements of GB/T15083-2006.
6. The flame retardant characteristics of all non-metals should meet the requirements of GB8410-2006.

Air Suspension Driver Seats For Heavy Plant Industry Vehicle Driver Seat Size:





15319910265



41318225@qq.com



vehicle-seats.com

140 meters west of intersection of Sunwu Road and Lane 4, Zhongjie, Weiyang District, Xi 'an, Shaanxi, China